

Displacement limiter V14-160

Setting angle [degree]	Displacement [cm ³ /varv]	Shim maximum side [mm]	Shim minimum side [mm]		Setting angle [degree]	Displacement [cm ³ /varv]	Shim maximum side [mm]	Shim minimum side [mm]
6,5	31,6	69,5	0,0		20,1	96	39,5	30,0
6,6	32	69,0	0,0		20,3	97	39,0	30,5
6,8	33	68,5	0,5		20,5	98	38,5	31,0
7,0	34	68,0	1,0		20,8	99	38,0	31,5
7,2	35	67,5	1,5		21,0	100	37,5	32,0
7,4	36	67,5	2,0		21,2	101	37,0	32,5
7,6	37	67,0	2,5		21,4	102	36,5	33,0
7,8	38	66,5	3,0		21,6	103	36,0	33,5
8,0	39	66,0	3,0		21,9	104	35,5	34,0
8,2	40	65,5	3,5		22,1	105	35,0	34,5
8,4	41	65,0	4,0		22,3	106	34,5	35,0
8,7	42	64,5	4,5		22,5	107	34,0	35,5
8,9	43	64,0	5,0		22,8	108	33,0	36,0
9,1	44	64,0	5,5		23,0	109	32,5	36,5
9,3	45	63,5	6,0		23,2	110	32,0	37,0
9,5	46	63,0	6,5		23,4	111	31,5	37,5
9,7	47	62,5	6,5		23,6	112	31,0	38,0
9,9	48	62,0	7,0		23,9	113	30,5	39,0
10,1	49	61,5	7,5		24,1	114	30,0	39,5
10,3	50	61,0	8,0		24,3	115	29,5	40,0
10,5	51	60,5	8,5		24,5	116	29,0	40,5
10,7	52	60,0	9,0		24,8	117	28,0	41,0
10,9	53	60,0	9,5		25,0	118	27,5	41,5
11,2	54	59,5	10,0		25,2	119	27,0	42,0
11,4	55	59,0	10,0		25,5	120	26,5	42,5
11,6	56	58,5	11,0		25,7	121	26,0	43,5
11,8	57	58,0	11,0		25,9	122	25,5	44,0
12,0	58	57,5	11,5		26,1	123	25,0	44,5
12,2	59	57,0	12,0		26,4	124	24,0	45,0
12,4	60	56,5	12,5		26,6	125	23,5	45,5
12,6	61	56,0	13,0		26,8	126	23,0	46,0
12,8	62	56,0	13,5		27,1	127	22,5	47,0
13,0	63	55,5	14,0		27,3	128	22,0	47,5
13,3	64	55,0	14,5		27,5	129	21,0	48,0
13,5	65	54,5	15,0		27,7	130	20,5	48,5
13,7	66	54,0	15,5		28,0	131	20,0	49,5
13,9	67	53,5	15,0		28,2	132	19,5	50,0
14,1	68	53,0	16,0		28,4	133	18,5	50,5
14,3	69	52,5	16,5		28,7	134	18,0	51,0
14,5	70	52,0	17,0		28,9	135	17,5	52,0
14,7	71	51,5	17,5		29,1	136	17,0	52,5
14,9	72	51,0	18,0		29,4	137	16,0	53,0
15,2	73	50,5	18,5		29,6	138	15,5	53,5
15,4	74	50,0	19,0		29,9	139	15,0	54,5
15,6	75	49,5	19,5		30,1	140	14,0	55,0
15,8	76	49,0	20,0		30,3	141	13,5	55,5
16,0	77	49,0	20,5		30,6	142	13,0	56,5
16,2	78	48,5	21,0		30,8	143	12,0	57,0
16,4	79	48,0	21,5		31,0	144	11,5	57,5
16,6	80	47,5	22,0		31,3	145	11,0	58,5
16,9	81	47,0	22,5		31,5	146	10,0	59,0
17,1	82	46,5	23,0		31,8	147	9,5	59,5
17,3	83	46,0	23,5		32,0	148	9,0	60,5
17,5	84	45,5	24,0		32,3	149	8,0	61,0
17,7	85	45,0	24,5		32,5	150	7,5	62,0
17,9	86	44,5	25,0		32,7	151	7,0	62,5
18,2	87	44,0	25,5		33,0	152	6,0	63,0
18,4	88	43,5	26,0		33,2	153	5,5	64,0
18,6	89	43,0	26,0		33,5	154	4,5	64,5
18,8	90	42,5	26,5		33,7	155	4,0	65,5
19,0	91	42,0	27,0		34,0	156	3,0	66,0
19,2	92	41,5	27,5		34,2	157	2,5	67,0
19,5	93	41,0	28,0		34,5	158	1,5	67,5
19,7	94	40,5	28,5		34,7	159	1,0	68,5
19,9	95	40,0	29,0		35,0	160	0,0	69,0