

18095

HJV

QRSPT $\frac{1}{2}$ " AH

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATA

OPTION:

AIRHEAD SIZE:

01

COMMENTS: 72" airhead

AIRHEAD OPTIONS:

MECHANICAL LEAVING
 EXHAUST DEFLECTOR

COMMENTS:

ENGINE MAKE OPTION:

QSX-15 LITER 600 HP CUMMINS TIER 4 FINAL

COMMENTS:

650hp? Size and location of
 def tank, size of fuel tank. In
 cab momentary shutoff on
 Hydraulic cooling Fan. Also
 install tap before motor on
 cooling fan to manually
 switch off. 2100RPM

ENGINE ADD-ONS:

REVERSING FAN

COMMENTS:

REAR TIRES:

1050/50 R32 TRELLEBORG

COMMENTS:

FRONT TIRES:

14.00 X 24 X 16

COMMENTS:

REAR WHEEL MOTORS:

ESKRIDGE 600

COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

FRONT WHEEL MOTORS:	MS18+20 POCLAIN	COMMENTS:
GROUND DRIVE:	ELECTRONICALLY CONTROLLED PUMPS	COMMENTS:
MAX. DIGGING GROUND SPEED =	3. MPH	COMMENTS:
PRIMARY ROW SPACING:	36"	COMMENTS:
VINE COULTERS:	DOUBLE DISK COULTER 24" DIA DISK	COMMENTS:
DIGGER BLADE BRACKET:	ROCK GUARD	COMMENTS: 0
DIGGER BLADES:	REGULAR (STANDARD BLADE)	STRAIGHT POINT 12" LONG (STANDARD LENGTH)
		PLASTIC UNDER BLADE BEVELED EDGE
		COMMENTS: bottom bevelled at 45 degrees to a point, see picture
CENTER BLADES:	15" LONG	BEVELED EDGE
		COMMENTS: Bevelled on bottom side 45degrees same as main blade
PRIMARY BED OPTIONS:	FULL WIDTH SIDE TO SIDE CONTROL	

SERIAL NUMBER: 19095 **AFF** **2019**
CUSTOMER: dave vanderzag **4 ROW SELF PROPELLED**
DEALER: **AIRHEAD HARVESTER**
SALESPERSON: **DATE:**

OPTION:

PRIMARY PLATES - 4" EXTENSION ON OUTSIDE NOSE STAINLESS STEEL ON PRIMARY, WELDED TO OUTSIDE	1" THICK OUTSIDE LOWER PRIMARY PLATES 3/4" THICK CENTER LOWER PRIMARY RIBS	COMMENTS: hyd hump in primary
PRIMARY DRIVE: REVERSE DRIVE		COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

PRIMARY GEARBOX OPTION: 6,000 HYDRAULIC MOTOR W/ GEAR BOX

COMMENTS:

VIBRATOR OPTIONS: ROCKING HYDRAULIC SHAKER - PRIMARY
 NO LOWER PRIMARY VIBRATOR

COMMENTS:

? Can you put rocking shaker in secondary? Yes
 Will be ran independantly from primary shaker.

PRIMARY BED CHAINS:

SINGLE WIDTH BELTED

WIDTH:

34" CHAIN (SINGLE WIDTH-USE W/36" ROWS)

PATTERN:

50MM 2 DOWN & 1 STRAIGHT

STANDARD CENTER TO CENTER DIGGERNOSE DISTANCE - FOR CHAIN SELECTED =

142-1/4

CHANGE DIGGERNOSE CENTER TO CENTER DISTANCE TO :

142-1/4

FRAME INSIDE DIMENSION (BASED SEC. CHAIN) =

142 1/2

VERIFY W/ SEC. CHAIN

COMMENTS:

All belts on harvester will have high cam belting

FRAME ROW WIDTH 36. INCHES

SECONDARY GEARBOX OPTION: 6,000 HYDRAULIC MOTOR W/ GEAR BOX

COMMENTS:

SECONDARY BED CHAINS:

FULL WIDTH BELTED SRT

69.00

PATTERN:

50MM ALL STRAIGHT SRT

BASE ROD

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

COMMENTS: 50 mm bare chain, with 1/2
 inch rod, machine is 2ft
 longer, use 1.5 ft extra and
 make secondary longer

2ND SECONDARY - STAR TABLE OPTIONS: AFE TABLE - 6 STARS W/ 2 ADJ. SMOOTH ROLLS AND DISTRIBUTOR STARS ON CROSS, 1ST 2 SHAFTS HAVE SINGLE BRG IN MIDDLE

STAR/AFE TABLE DRIVE MOTOR OPTION: 2000 SERIES
 STAR SPECIFICATIONS: NOFFSINGER 70DURO 14PT
 NOTE: SHORT SIDE ENDS W/ 3 STARS
 AFE SMOOTH ROLL OPTION: 6" DIAMETER

COMMENTS:

2ND SECONDARY GEARBOX OPTION: NO 2ND SECONDARY
 PATTERN:

COMMENTS:

DEVINER GEARBOX OPTION: 6,000 HYDRAULIC MOTOR W/ GEAR BOX

COMMENTS:

DEVINER/OVERRIDE CHAIN: 150MM

COMMENTS: Steel scrapers on deviner
 return rollers

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

LOWER SIDE ELEVATOR AFE STAR TABLE OPTION: NO AFE STAR TABLE

OTHER STANDARD PATTERN = ALL STRAIGHT SRT
 STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS:

LOWER SIDE = 2 CHAINS
 2 segment roll shafts, spirals
 twisting out, 1 adjustable
 (ratchet turnbuckle each
 side) steel 6" roller all driven
 off of one motor. Location at
 top directly before airhead.
 chain is 45mm RC. Speed
 control separate from side
 delivery located before and
 after these rollers.

TOP SIDE ELEVATOR VINEBELT OR AIRKNIFE OPTION: AIR KNIFE W/ 10" CRARY BLOWER (600HP REQ'D)

STAR SPECIFICATIONS:
 NOFFSINGER 55DURO 14PT

45MM STANDARD PATTERN = 10 DOWN 1 STRAIGHT SRT
 STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS: 0

COMMENTS: Standard Pattern.

MULTI-SEP / M-TABLE OPTION: 72" MULTI-SEP

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

COMMENTS: Distribution stars between
 multisep and bin fill chain
 need bearings spaced farther
 apart. Up to 6" if it doesn't
 make machine wider than
 24ft

BIN OPTIONS: LARGE BIN (80-100 BAG) W/ FILL CONV SONIC CONTROL

BIN BELT: 40" WIDE FLAT PVC

OF SONIC SENSORS: 2 SENSORS

COMMENTS: can Bin be made wider? We
 have given you are wides
 bin. Dirt builds- install white
 plastic on angled bottom of
 bin and on the bin wall on
 discharge side. Or bin fill
 conveyor 4" shorter as it
 overflows out boom today
 and back of bin is empty??
 We are going to add a bin
 door, can back of bin be a
 little lower toys walk
 over?yes Bin doors always
 get bent- solution??

BIN FILL: 40" BIN FILL CONVEYOR
 45MM STANDARD PATTERN = 3 DOWN 1 STRAIGHT SRT

SERIAL NUMBER: 19095 **AFE** **2019**
CUSTOMER: dave vanderzag **4 ROW SELF PROPELLED**
DEALER: **AIRHEAD HARVESTER**
SALESPERSON: **DATE:**

OPTION:

STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS:

chain all straight rubber covered Make manual flip up bin extensions front and back to fill bin more in field, flip down for road and storage.

SERIAL NUMBER: 19095

AFE 2019

CUSTOMER: dave vanderzag

4 ROW SELF PROPELLED

DEALER:

AIRHEAD HARVESTER

SALESPERSON:

DATE:

OPTION:

BULK LOADER: 40" WIDE

PATTERN: OTHER

STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS:

Make inner boom 8" longer
OK, chain height is to be 9'8"
new height is 117" from floor
at base of boom; if different
discuss.

REVERSE DRIVE('S' DRIVE SPROCKETS):

Can boom sides be 4" taller
Yes on inter boom bolt on so
when bulk hopper unloads it
does not spill

Leave bracket for plastic rock
pan in boom but ship plastic
seperate not installed

STONE BOX OPTIONS: FOLD-OVER (OUTSIDE HALF) STONE BOX

COMMENTS:

STONE CONVEYOR CHAIN: BELTED CHAIN

OPTIONS: SOLID FLOOR - OPEN UNDER AIRHEAD

COMMENTS:

CHAIN ROLLER OPTIONS: (SPECIFY LOCATIONS)

GRIMME

COMMENTS:

Steel standard nose roller?
Matches scrapers

SERIAL NUMBER: 19095

AFE 2019

CUSTOMER: dave vanderzag

4 ROW SELF PROPELLED

DEALER:

AIRHEAD HARVESTER

SALESPERSON:

DATE:

OPTION:

--

SERIAL NUMBER: 19095 AFE 2019
CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
DEALER: AIRHEAD HARVESTER
SALESPERSON: DATE:

OPTION:

BOLT/NUT OPTIONS: USE SPIN LOCK NUTS

COMMENTS:

WORK PLATFORMS:

COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

FLOW CONTROLS:

PRIMARY - ELECTRONIC CONTROLS -
 SECONDARY/DEVINER - ELECTRONIC CONTROLS -
 AFE TABLE-FLOW CONTROL W/ACTUATOR

ADD REVERSING
 ADD REVERSING
 ADD LT/RT/DIST REVERSING

COMMENTS:
 COMMENTS:
 COMMENTS: Need actuator-in-cab-for deviner/secondary speed

CROSS CONVEYOR

FLOW CONTROL W/ ACTUATOR

COMMENTS: **NEED ACTUATOR IN CAB

CROSS STAR TABLE OPTION
 CROSS DISTRIBUTOR STARS

NO STAR TABLE/FLOW CONTROL
 FLOW CONTROL W/ ACTUATOR

COMMENTS:
 COMMENTS:
 COMMENTS:

AIRHEAD FEED - FLOW CONTROL W/ ACTUATOR
 STONE CONVEYOR

MANUAL FLOW CONTROL
 FLOW CONTROL W/ ACTUATOR

COMMENTS: Side delivery immediately before segment rollers and after segment rollers before stone chain will have separate speed controls- 2

AIRHEAD DISCHARGE CONVEYOR

flow control with actuator in cab. * Airhead discharge conveyor also adjustable from cab **Build flap so no potatoes roll back onto airhead skirt. See pics attached.

VINEBELT FEED STARS - MANUAL FLOW CONTROL
 VINEBELT FEED STEEL ROLL - MANUAL FLOW CONTROL
 VINEBELT DRIVE - MANUAL FLOW CONTROL

COMMENTS:
 COMMENTS:
 COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

VINEBELT/MULTI-SEP/M-TABLE DIST ROLLS - MANUAL FLOW CON

COMMENTS: Multisep needs flow control

and reverser in cab. Smooth
rollers on multisep can be
manually set to run reverse
or forward outside of cab.

BIN FILL/SORT TABLE

MANUAL FLOW CONTROL

COMMENTS:

BIN UNLOAD - FLOW CONTROL W/ ACTUATOR

FLOW CONTROL W/ ACTUATOR

COMMENTS:

Other

COMMENTS:

CAB OPTIONS:

JOHN DEERE OEM CAB

* CLIMATE CONTROL (2030-02177)

MAX. CAB (HARVESTER) HEIGHT = 172. INCHES

CAB EXTENSIONS (~MAX HEIGHT)

MECHANICAL HYDRAULIC PRESSURE GAUGES

SERIAL NUMBER: 19095

AFE 2019

CUSTOMER: dave vanderzag

4 ROW SELF PROPELLED

DEALER:

AIRHEAD HARVESTER

SALESPERSON:

DATE:

OPTION:

4 - COLOR CAMERAS (SPECIFY LOCATION)

COMMENTS:

Does OEM cab have LED lighting? Yes I believe so I added cab Extension in will make cab as tall as the bin about a 8-10 lift. Camera locations: 1. Backup cam 2. Rear cross 3. Airhead stone discharge 4. Multisep

Loud horn mounted beside stone box, button for it on back of remote.

MAX WIDTH NO WIDER THAN 24ft

CAB/BIN NO HIGHER THAN 167 inches

End of Rear cross on side sheet metal

Back of Sep. having forward

SERIAL NUMBER: 19095 AFE 2019
CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
DEALER: AIRHEAD HARVESTER
SALESPERSON: DATE:

OPTION:

EXTRA OPTIONS:

GRATING ALONG CAB: BAR GRATING (2-3/8x4)

COMMENTS: 0

Additional Comments: Fuel/Def HAS to meet 12 hrs of runtime. Put well in center of tank for side hills***. Grimme clips with bushings on all belts, all belts hi-cam***. No wider than 24ft. With airhead folded down, no higher than 13 ft 11 inches.

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

AIRHEAD SIZE: OTHER:

COMMENTS: 72" airhead

AIRHEAD OPTIONS: MECHANICAL LEVELING

EXHAUST DEBRIS DEFLECTOR

COMMENTS:

ENGINE MAKE OPTION: QSX-15 LITER 600 HP CUMMINS TIER 4 FINAL

COMMENTS: 650hp? Size and location of

def tank, size of fuel tank. In
 cab momentary shutoff on
 Hydraulic cooling Fan. Also
 install tap before motor on
 cooling fan to manually
 switch off. 2100RPM

X
 TC115

ENGINE ADD-ONS: REVERSING FAN

COMMENTS:

REAR TIRES: 1050/50 R32 TRELLEBORG

COMMENTS:

FRONT TIRES: 14.00 X 24 X 16

COMMENTS:

THIS HAS CHANGED

REAR WHEEL MOTORS: ESKRIDGE 600

COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

FRONT WHEEL MOTORS:	MS18+20 POCLAIN	COMMENTS:
GROUND DRIVE:	ELECTRONICALLY CONTROLLED PUMPS	COMMENTS:
MAX. DIGGING GROUND SPEED =	3. MPH	COMMENTS:
PRIMARY ROW SPACING:	36"	COMMENTS:
VINE COULTERS:	DOUBLE DISK COULTER 24" DIA DISK	COMMENTS:
DIGGER BLADE BRACKET:	ROCK GUARD	COMMENTS: 0
DIGGER BLADES:	REGULAR (STANDARD BLADE)	STRAIGHT POINT 12" LONG (STANDARD LENGTH)
		PLASTIC UNDER BLADE
		BEVELED EDGE
		COMMENTS: bottom bevelled at 45 degrees to a point, see picture
CENTER BLADES:	15" LONG	BEVELED EDGE
		COMMENTS: Bevelled on bottom side 45degrees same as main blade
PRIMARY BED OPTIONS:	FULL WIDTH SIDE TO SIDE CONTROL	

SERIAL NUMBER: 19095 **AFE** **2019**
CUSTOMER: dave vanderzag **4 ROW SELF PROPELLED**
DEALER: **AIRHEAD HARVESTER**
SALESPERSON: **DATE:**

OPTION:

PRIMARY PLATES - 4" EXTENSION ON OUTSIDE NOSE STAINLESS STEEL ON PRIMARY, WELDED TO OUTSIDE	1" THICK OUTSIDE LOWER PRIMARY PLATES 3/4" THICK CENTER LOWER PRIMARY RIBS
PRIMARY DRIVE: REVERSE DRIVE	COMMENTS: hyd hump in primary
COMMENTS:	

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

PRIMARY GEARBOX OPTION: 6,000 HYDRAULIC MOTOR W/ GEAR BOX

COMMENTS:

VIBRATOR OPTIONS: ROCKING HYDRAULIC SHAKER - PRIMARY
NO LOWER PRIMARY VIBRATOR

COMMENTS: ? Can you put rocking shaker in secondary? Yes Will be ran independantly from primary shaker.

PRIMARY BEED CHAINS: SINGLE WIDTH BELTED

WIDTH: 34" CHAIN (SINGLE WIDTH-USE W/36" ROWS)

PATTERN: 50MM 2 DOWN & 1 STRAIGHT

STANDARD CENTER TO CENTER DIGGERNOSE DISTANCE - FOR CHAIN SELECTED = 142-1/4

CHANGE DIGGERNOSE CENTER TO CENTER DISTANCE TO : 142-1/4

FRAME INSIDE DIMENSION (BASED SEC. CHAIN) = 142 1/2

FRAME ROW WIDTH 36. INCHES

VERIFY W/ SEC. CHAIN

COMMENTS:

All belts on harvester will have high cam belting

SECONDARY GEARBOX OPTION: 6,000 HYDRAULIC MOTOR W/ GEAR BOX

COMMENTS:

SECONDARY BED CHAINS: FULL WIDTH BELTED SRT

PATTERN: 50MM ALL STRAIGHT SRT

69.00

BAZE ROD SHIP w/ PARTS LOAD

SERIAL NUMBER: 19095 AFE 2019
CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
DEALER: AIRHEAD HARVESTER
SALESPERSON: DATE:

OPTION:

COMMENTS: 50 mm bare chain, with 1/2
inch rod, machine is 2ft
longer, use 1.5 ft extra and
make secondary longer

2ND SECONDARY - STAR TABLE OPTIONS: AFE TABLE - 6 STARS W/ 2 ADJ. SMOOTH ROLLS AND DISTRIBUTOR STARSON CROSS, 1ST 2 SHAFTS HAVE SINGLE BRG IN MIDDLE

STAR/AFE TABLE DRIVE MOTOR OPTION: 2000 SERIES
STAR SPECIFICATIONS: NOFFSINGER 70DURO 14PT
NOTE: SHORT SIDE ENDS W/ 3 STARS
AFE SMOOTH ROLL OPTION: 6" DIAMETER

COMMENTS:

2ND SECONDARY GEARBOX OPTION: NO 2ND SECONDARY
PATTERN:

COMMENTS:

DEVINER GEARBOX OPTION: 6,000 HYDRAULIC MOTOR W/ GEAR BOX

COMMENTS:

DEVINER/OVERRIDE CHAIN: 150MM

COMMENTS: Steel scrapers on deviner
return rollers

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

REAR CROSS: 48" WIDE CROSS NO LEVELING SYSTEM

PATTERN: 45MM

SHORT SIDE: 2nd last shaft is centered on edge of rear cross; 6" drop from center of shaft to rear cross belt;
 ON LONG SIDE : 4" drop from center of last shaft to rear cross belt; last star 2" down from rest, second last star 1" down from rest; 20" overhang on rear cross (3 stars)

COMMENTS:

Add "C" flex on rear cross chain, add stainless steel on side along tapered stars.
 Spread bearings out 6"
 additional wide on tapered stars to hold them better,
 add 2 more tapered stars to spread crop on side elevator.

SECONDARY/AFE TABLE TO CROSS DROP DISTANCE = ? inches

REAR CROSS TABLE OPTION: NO STAR TABLE - CHAIN ONLY

COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

LOWER SIDE ELEVATOR AFE STAR TABLE OPTION: NO AFE STAR TABLE

OTHER STANDARD PATTERN = ALL STRAIGHT SRT
 STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS:

2 segment roll shafts, spirals
 twisting out, 1 adjustable
 ratchet turnbuckle each
 side) steel 6" roller all driven
 off of one motor. Location at
 top directly before airhead.
 chain is 45mm RC. Speed
 control separate from side
 delivery located before and
 after these rollers.

LOWER SIDE = 2 CHAINS

TOP SIDE ELEVATOR VINEBELT OR AIRKNIFE OPTION: AIR KNIFE W/ 10" CRARY BLOWER (600HP REQ'D)

STAR SPECIFICATIONS:
 NOFINGER 55DURO 14PT

COMMENTS: 0

45MM STANDARD PATTERN = 10 DOWN 1 STRAIGHT SRT
 STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS: Standard Pattern.

MULTI-SEP / M-TABLE OPTION: 72" MULTI-SEP

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

BIN OPTIONS: LARGE BIN (80-100 BAG) W/ FILL CONV SONIC CONTROL

BIN BELT: 40" WIDE FLAT PVC
OF SONIC SENSORS: 2 SENSORS

COMMENTS: Distribution stars between

multisep and bin fill chain
need bearings spaced farther
apart. Up to 6" if it doesn't
make machine wider than
24ft

COMMENTS: can Bin be made wider? We

have given you are wides
bin. Dirt builds- install white
plastic on angled bottom of
bin and on the bin wall on
discharge side. Or bin fill
conveyor 4" shorter as it
overflows out boom today
and back of bin is empty??
We are going to add a bin
door, can back of bin be a
little lower toys walk
over?yes Bin doors always
get bent- solution??

BIN FILL: 40" BIN FILL CONVEYOR
45MM STANDARD PATTERN = 3 DOWN 1 STRAIGHT SRT

SERIAL NUMBER: 19095

AFE 2019

CUSTOMER: dave vanderzag

4 ROW SELF PROPELLED

DEALER:

AIRHEAD HARVESTER

SALESPERSON:

DATE:

OPTION:

STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS:

chain all straight rubber covered Make manual flip up bin extensions front and back to fill bin more in field, flip down for road and storage.

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

BULK LOADER: 40" WIDE

PATTERN: OTHER

STANDARD CONVEYOR STYLE = UHMW SLIDES

COMMENTS: Make inner boom 8" longer

OK, chain height is to be 9'8"
new height is 117" from floor
at base of boom; if different
discuss.

REVERSE DRIVE('S' DRIVE SPROCKETS):

Can boom sides be 4" taller
Yes on inter boom bolt on so
when bulk hopper unloads it
does not spill

STONE BOX OPTIONS: FOLD-OVER (OUTSIDE HALF) STONE BOX

COMMENTS:

Leave bracket for plastic rock
pan in boom but ship plastic
seperate not installed

STONE CONVEYOR CHAIN: BELTED CHAIN
OPTIONS: SOLID FLOOR - OPEN UNDER AIRHEAD

COMMENTS:

CHAIN ROLLER OPTIONS: (SPECIFY LOCATIONS)

GRIMME

COMMENTS: Steel standard nose roller?

Matches scrapers

SERIAL NUMBER: 19095

AFE 2019

CUSTOMER: dave vanderzag

4 ROW SELF PROPELLED

DEALER:

AIRHEAD HARVESTER

SALESPERSON:

DATE:

OPTION:

--

SERIAL NUMBER: 19095 AFE 2019
CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
DEALER: AIRHEAD HARVESTER
SALESPERSON: DATE:

OPTION:

USE SPIN LOCK NUTS

COMMENTS:

BOLT/NUT OPTIONS:

WORK PLATFORMS:

COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

FLOW CONTROLS:

PRIMARY - ELECTRONIC CONTROLS -	ADD REVERSING	COMMENTS:
SECONDARY/DEVINER - ELECTRONIC CONTROLS -	ADD REVERSING	COMMENTS:
AFE TABLE-FLOW CONTROL W/ACTUATOR	ADD LT/RT/DIST REVERSING	COMMENTS: Need actuator in cab for deviner/secondary speed
CROSS CONVEYOR	FLOW CONTROL W/ ACTUATOR	COMMENTS: **NEED ACTUATOR IN CAB
CROSS STAR TABLE OPTION	NO STAR TABLE/FLOW CONTROL	COMMENTS:
CROSS DISTRIBUTOR STARS	FLOW CONTROL W/ ACTUATOR	COMMENTS:
AIRHEAD FEED - FLOW CONTROL W/ ACTUATOR	MANUAL FLOW CONTROL	COMMENTS:
STONE CONVEYOR	FLOW CONTROL W/ ACTUATOR	COMMENTS: Side delivery immediately before segment rollers and after segment rollers before stone chain will have separate speed controls- 2 flow control with actuator in cab. *Airhead discharge conveyor also adjustable from cab **Build flap so no potatoes roll back onto airhead skirt. See pics attached.
AIRHEAD DISCHARGE CONVEYOR		COMMENTS:
VINEBELT FEED STARS - MANUAL FLOW CONTROL		COMMENTS:
VINEBELT FEED STEEL ROLL - MANUAL FLOW CONTROL		COMMENTS:
VINEBELT DRIVE - MANUAL FLOW CONTROL		COMMENTS:

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

VINEBELT/MULTI-SEP/M-TABLE DIST ROLLS - MANUAL FLOW CON

COMMENTS: Multisep needs flow control

and reverser in cab. Smooth rollers on multisep can be manually set to run reverse or forward outside of cab.

BIN FILL/SORT TABLE

MANUAL FLOW CONTROL

COMMENTS:

BIN UNLOAD - FLOW CONTROL W/ ACTUATOR

FLOW CONTROL W/ ACTUATOR

COMMENTS:

Other

COMMENTS:

CAB OPTIONS:

JOHN DEERE OEM CAB

CLIMATE CONTROL (2030-02177)

MAX. CAB (HARVESTER) HEIGHT = 172. INCHES

CAB EXTENSIONS (~MAX HEIGHT)

MECHANICAL HYDRAULIC PRESSURE GAUGES

SERIAL NUMBER: 19095 AFE 2019
 CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
 DEALER: AIRHEAD HARVESTER
 SALESPERSON: DATE:

OPTION:

4 - COLOR CAMERAS (SPECIFY LOCATION)

COMMENTS: Does OEM cab have LED

lighting? Yes I believe so I added cab Extension in will make cab as tall as the bin about a 8-10 lift. Camera locations: 1. Backup cam 2. Rear cross 3. Airhead stone discharge 4. Multisep
 Loud horn mounted beside stone box, button for it on back of remote.
 MAX WIDTH NO WIDER THAN 24ft
 CAB/BIN NO HIGHER THAN 167 inches

End of Rear cross on side sheet metal

Back of Self-holding Forward

SERIAL NUMBER: 19095 AFE 2019
CUSTOMER: dave vanderzag 4 ROW SELF PROPELLED
DEALER: AIRHEAD HARVESTER
SALESPERSON: DATE:

OPTION:

EXTRA OPTIONS:

GRATING ALONG CAB: BAR GRATING (2-3/8X4)

COMMENTS: 0

Additional Comments: Fuel/Def HAS to meet 12 hrs of runtime. Put well in center of tank for side hills***
Grimme clips with bushings on all belts, all belts hi-cam***. No wider than 24ft. With airhead folded down, no higher than 13 ft 11 inches.